



WL060

Straight to mains LED halo / flood wall light

Features

IP Rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

UK Bathroom Zone	2
Inrush Current	9A 0.8ms
Construction Material	Anodised aluminium
Weight	0.6kg
Ambient Temperature Range	40°C
SELV	Yes
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL060 NW	Silver	2.6W	4000K	120°	82	32	46
WL060 WW	Silver	2.6W	3000K	120°	58	22	26
WL060 27	Silver	2.6W	2700K	120°	56	22	25

Energy rating is a reflection of the LED light source.

Wiring information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A
------------------------------	----------	-----	----	---	-----	-----

Accessories

N/A (No Accessories required)
-------------------------------



01604 495 151  
 collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 years

Features & benefits

- 2.6W
- Coastal protected
- IP65 ideal for outdoor environments
- Bi-directional wall light offering decorative halo effect and functional downward flood light
- Complete with wall fixings and waterproof crimp connectors
- Mains voltage wall light

Light source  
 energy efficiency:



Beam angle: 120°

