Tel: +44 2476 368 500
Email: lv.enquiries@gb.abb.com

E4.2N 3200 Ekip Dip LI 3p WMP

Cat Number: 1SDA072491R1





MOVING PART FOR C.BREAKER SACE EMAX2 E4.2N 3200 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LI R 3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Technical Specifications:
ABB EcoSolutions | Yes
Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available
RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP | 5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy (IT)
Order Code US and Canada | Z4NVENAA000A000000XX
EAN | 8015644763411
Minimum Order Quantity | 1 piece
Customs Tariff Number | 85362090
Product Net Width | 425 mm
Product Net Height | 425 mm
Product Net Depth / Length | 383 mm
Product Net Weight | 60 kg
Package Level 1 Units | box 1 piece

Powered by
OneTimePIM
www.OneTimePIM.com

Tel: +44 2476 368 500
Email: lv.enquiries@gb.abb.com

Package Level 1 Width | 515 mm
Package Level 1 Height | 610 mm
Package Level 1 Depth / Length | 615 mm
Package Level 1 Gross Weight | 67 kg
Package Level 1 EAN | 8015644763411
Current Type | AC
Electrical Durability | Ue =< 440 V 7000 cycleUe = 500 ... 690 V 7000 cycle20 cycles per hour
Mechanical Durability | 20000 cycle60 cycles per hour
Number of Poles | 3
Power Loss | 743 W
Product Main Type | SACE Emax 2
Product Name | Air Circuit Breaker
Product Type | Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (Ics) | 100 %
Rated Current (In) | 3200 A
Rated Voltage (Ur) | 690 V
Rated Impulse Withstand Voltage (Uimp) | acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (Ui) | AC 1000 V
Rated Operational Voltage | 690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics) | (220 V AC) 66 kA(230 V AC) 66 kA(380 V AC) 66 kA(400 V AC) 66 kA(415 V AC) 66 kA(440 V AC) 66 kA(500 V AC) 66 kA(660 V AC) 66 kA(690 V AC) 66 kA
Rated Short-time Withstand Current Low Voltage (Icw) | for 1 s 66 kAfor 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (Icu) | (400 V AC) 66 kA(415 V AC) 66 kA(440 V AC) 66 kA(500 V AC) 66 kA(525 V AC) 66 kA(690 V AC) 66 kA
Rated Uninterrupted Current (Iu) | 3200 A
Release | Ekip Dip LI
Release Type | EL
Short-Circuit Performance Level | N
Standards | IEC
Sub-type | E4.2
Version | W
ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers

Powered by
OneTimePIM
www.OneTimePIM.com

Tel: +44 2476 368 500
Email: lv.enquiries@gb.abb.com

Object Classification Code | Q
UNSPSC | 39121615
WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm)
eClass | V11.1 : 27370409

Powered by
OneTimePIM
www.OneTimePIM.com