

S2C-CM4 S200 4P MOTOR OPERATOR

Cat Number: 2CSS204997R0013



Motor operating devices

* Part number: S2C-CM4

* Function: S2C-CM, F2C-CM and DS2C-CM allow the remote control (opening or closing) of the coupled device. Suitable for S200 MCBs up to 63 A, F 200 RCCBs up to 100 A and RCBOs DS201 and DS202C.

Technical Specifications:

Suitable For I S204PS304P

Suitable for Product Class I Miniature Circuit Breakers MCBs

Rated Voltage (Ur) I 12 V

Operational Voltage I 12 ... 30 +10% -15% V AC 12 ... 48 +10% -15% V DC

Input Voltage Type I AC/DC

Rated Frequency (f) I AC 50 ... 60 Hz

Power Consumption (@Pcons) I 12 V AC - < 16 V·A 24 V AC - < 27 V·A 30 V AC - < 28 V·A 12...48 V DC - < 22 V·A

Power Loss I 1.5 W

Electrical Endurance I 20000 cycle

Number of Contacts CO I 1

Number of Contacts NC I 0

Number of Contacts NO I 0

Number of Auxiliary Contacts CO (SPDT) | 1

Mounting Type | DIN-Rail

Connecting Capacity | 2.5 mm²

Terminal Type | Screw Terminals

Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C

Degree of Protection | Enclosure with Cover IP20

Pollution Degree | 2

RoHS Status | Following EU Directive 2011/65/EU

Product Net Width | 36 mm

Product Net Height | 0.089 m

Product Net Depth / Length | 0.081 m

Product Net Weight | 0.173 kg

Minimum Order Quantity | 1 piece

Package Level 1 Units | box 1 piece

Package Level 1 Gross Weight | 0.242 kg

E-Number (Sweden) | 2102494

ETIM 8 | EC001286 - Auxiliary device for distribution board devices

ETIM 9 | EC001286 - Auxiliary device for distribution board devices

WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B | Business To Consumer

CN8 | 85365080

eClass | V11.0 : 27143502

Object Classification Code | Q