



Tel: 01709 704000
Email: csd@rittal.co.uk

SK ENCLOSURE HEATER 18 - 20W REPLACES 3106120 AND

Cat Number: 3105320



Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits. Version without fan. Continuous thermal output 10 – 150 W.

Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits.

SK enclosure heater, without fan, 18-20 W, 110-240 V, 1~, 50/60 Hz, WHD: 45 x 120 x 46 mm

Technical Specifications:

Article number: | SK 3105.320

Material | Aluminium, anodised

Supply includes | PTC heater

Quick-connection terminal

Assembly parts

Note | A thermostat is recommended for precise temperature control inside the enclosure.

Powered by

OneTimePIM
www.OneTimePIM.com



Tel: 01709 704000
Email: [csd @rittal.co.uk](mailto:csd@rittal.co.uk)

Note on Model No. | null

Continuous thermal output at 10 °C | 18 W ÷ 20 W

Rated operating voltage | 110 V - 240 V, 1~, 50 Hz/60 Hz

Dimensions | Width: 45 mm

Height: 120 mm

Depth: 46 mm

Pre-fuse | Miniature circuit-breaker/fuse: 2 A

IP protection category to IEC 60 529 | IP 20

Protection class | II (all-insulated)

Operating temperature range | -33 °C...65 °C

Packs of | 1 pc(s).

Weight/pack | 0.22 kg

Customs tariff number | 85162999

EAN | 4028177638624

ETIM 7.0 | EC000737

ECLASS 8.0 | 27180710

Powered by

OneTimePIM
www.OneTimePIM.com