



Tel: 01709 704000
Email: [csd @rittal.co.uk](mailto:csd@rittal.co.uk)

VX IT STD. RAL 7035 WHD 800X2200X1000

Cat Number: 5314126



VX IT network/server enclosure, closed, for direct climate control tailored to the specific enclosure. 482.6 mm (19") interior installation with depth-variable 482.6 mm (19") mounting angles in the standard version, available in a range of size variants.

VX IT, 19" mounting angles, standard, front and rear, glazed door, WHD: 800 x 2200 x 1000 mm, 47 U

Technical Specifications:

Article number: | VX 5314.126

Material | Sheet steel

Aluminium

Glazed door: Single-pane safety glass, 3 mm

Surface finish | Enclosure frame: Dipcoat-primed

Interior installation: Spray-finished

Rear door and roof: Dipcoat-primed, powder-coated

Front door: Aluminium, anodised/spray-finished

Colour | Enclosure frame, rear door and roof: RAL 7035

Front door: Vertical sections, silver coloured and horizontal sections, RAL 9005

Powered by

OneTimePIM
www.OneTimePIM.com



Tel: 01709 704000
Email: [csd @rittal.co.uk](mailto:csd@rittal.co.uk)

Interior installation: RAL 9005

Handle and hinges: RAL 9005

Supply includes | VX enclosure frame with doors and roof plate

Glazed aluminium door at the front, 180° hinges

Lock front and rear: Comfort handle for profile half-cylinders and security lock 3524 E

Mounting angles, 482.6 mm (19")

Spacers, height 50 mm, to raise a cover plate above the fan cut-out in the roof plate, for passive cooling (supplied loose). Not required for variants without a cut-out.

12 x 482.6 mm (19") fastener, 1 U, conductive (supplied loose)

25 multi-tooth screws, conductive (supplied loose)

IPPC pallet

Roof plate, multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate

Sheet steel rear door, solid, vertically divided, 180° hinges

Dimensions | Width: 800 mm

Height: 2,200 mm

Depth: 1,000 mm

Units | 47 U

Free mounting space to the 482.6 mm (19") level, front/rear | 87 mm / 193 mm

Mounting position of the 482.6 mm (19") level | front and rear

Distance between levels as delivered | 720 mm

482.6 mm (19") attachment | on depth stays, screw-fastened at the top and bottom

Design | Standard

Cover version | multi-piece, with side cable entry in the depth, double-sided, prepared for fan mounting plate

Mounting angle version | 482.6 mm (19") mounting angles, standard in the VX IT

Base design | Open

482.6 mm (19") level(s) version | front and rear

Load capacity | 15,000 N

Max. load capacity (static) per enclosure to UL 2416 | 12,000 N

IK Code | IK08

Note | Depending on how and where it is sited, the door opening angle may vary for selected applications

Basic material | Sheet steel

Construction rear door | Sheet steel door, solid, vertically divided, 180° hinges

Powered by

OneTimePIM
www.OneTimePIM.com



Tel: 01709 704000
Email: [csd @rittal.co.uk](mailto:csd@rittal.co.uk)

Construction front door | Glazed aluminium door, solid, one-piece, 180° hinges

Packs of | 1 pc(s).

Weight/pack | 115 kg

EAN | 4028177945326

ETIM 7.0 | EC002499

ECLASS 8.0 | 27180207

Powered by

OneTimePIM
www.OneTimePIM.com