

37 Way Duplex Consumer Unit Main Switch 100A

Cat Number: 537/2B

37W Main switch only duplex consumer unit.

Includes a 100A main switch with twin line and neutral supply terminals and 100A insulated plug in busbar assemblies.

Accepts all Starbreaker miniature final circuit protection devices; MCBs, RCBOs and AFDDs. Accepts the Starbreaker miniature type 2 SPD SBT2SPD3W/1.

Constructed from a full metal enclosure with a temporary locking facility when installed in conjunction with the Crabtree locking bar CRDLBK.

Technical Specifications:

Mounting method | Surface mounted (plaster)

Number of phases | 1

Protection | Miniature- / earth leakage circuit breaker

Total number of groups | 1

Number of poles main switch | 2

Main switch rated current | 100 A

Over voltage protection | No

Material housing | Steel

Degree of protection (IP) | IP2XC

Powered by **OneTime PIM** www.OneTimePIM.com

electrium

Height | 506 mm Width | 440 mm Width in number of modular spacings | 20 Depth | 121 mm Extension possible | No With transparent cover | No Lockable | No Product Standard/s | BS EN 61439-3 Frequency | 50 Hz CE Conformity | Yes WEEE Symbol | Yes UKCA Conformity | Yes Amperage | 100 A Operating Voltage | 230 V Type of Current | AC Consumer Unit Type | Main switch only Total final circuit modular ways | 37 Busbar type | Plug in Main switch rating | 100 A Main switch final circuit modular ways | 37 Colour RAL | 9010

