

## 50A 2 Gang Double Pole Switch With LED

Cat Number: CR1501



Curved Slimline Plate.  
Integrated LED Light Indicator.  
Fully Rated to 50A.

### Technical Specifications:

Product Standard/s | BS EN 60669-1

Terminal Capacity L&N | 3 x 2.5, 2 x 4.0, 1 x 6.0, 1 x 10.0, 1 x 16.0 mm<sup>2</sup>

Terminal Capacity E | 3 x 2.5, 2 x 4.0, 1 x 6.0, 1 x 10.0, 1 x 16.0 mm<sup>2</sup>

Frequency | 50 Hz

LRV Value | 74

CE Conformity | Yes

WEEE Symbol | Yes

UKCA Conformity | Yes

Wiring system | 2-pole switch

Method of operation | Rocker/button

Assembly arrangement | Control element

Number of modules (module system) | 0

Push button switch | Yes

Number of rockers | 1  
Mounting method | Flush mounted (plaster)  
Type of fastening | Screw mounting  
With mounting plate | Yes  
Material | Plastic  
Material quality | Other  
Halogen free | Yes  
Surface protection | Other  
Surface finishing | Glossy  
Colour | White  
Illumination | Yes  
Function lighting | Illuminated (on)  
Type of lighting | Not included  
Suitable for degree of protection (IP) | IP2X  
Nominal voltage | 250 V  
Rated current | 50 A  
Connection type | Screwed terminal  
Width of device | 86 mm  
Height of device | 146 mm  
Depth of device | 38 mm  
Built-in depth | 47 mm  
Min. depth of built-in installation box | 47 mm