

13A Double Pole Switched Fused Connection Unit All Grey With

Cat Number: CR1827F/G



Curved Slimline Plate.

All Upward Facing Terminals.

Full Contact Cable Clamp.

Fitted With ASTA Approved Fused Link.

Technical Specifications:

Product Standard/s | BS 1363-4

Terminal Capacity L&N | 3 x 1.5, 3 x 2.5, 2 x 4.0 mm<sup>2</sup>

Terminal Capacity E | 1 x 1.5, 1 x 2.5 Solid, 1 x 0.5, 1 x 1.5 Flex mm<sup>2</sup>

Frequency | 50 Hz

LRV Value | 8

CE Conformity | Yes

WEEE Symbol | Yes

UKCA Conformity | Yes

Wiring system | 2-pole switch

Method of operation | Rocker/button

Assembly arrangement | Control element

Number of modules (module system) | 0

Push button switch | Yes  
Number of rockers | 1  
Mounting method | Flush mounted (plaster)  
Type of fastening | Screw mounting  
With mounting plate | Yes  
Material | Plastic  
Material quality | Other  
Halogen free | Yes  
Surface protection | Other  
Surface finishing | Glossy  
Colour | Grey  
Illumination | No  
Function lighting | Other  
Type of lighting | Not included  
Suitable for degree of protection (IP) | IP2X  
Nominal voltage | 250 V  
Rated current | 13 A  
Connection type | Screwed terminal  
Width of device | 86 mm  
Height of device | 86 mm  
Depth of device | 29 mm  
Built-in depth | 16 mm  
Min. depth of built-in installation box | 25 mm