


P/N: FR710-24MG3PF-XXX

2.4mm Male to G3PO (SMPS) Female Cable Assembly | .086" Semi-Rigid GUT-085 (Copper) Coax Cable | DC - 50GHz



Dimensions are in mm



Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.4mm	G3PO(SMPS)
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50.0	50.0
Connector Mount Method	None	None
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	CuBe
Connector Body Plating	Passivated	Gold

Cable Configuration

Cable Type	.086" Semi-rigid Cable (Copper)
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver plated copperweld
Dielectric Material	Solid PTFE
Shield Layer 1 Material	Copper
Cable Diameter (mm)	2.2
Cable Color	Cooper
Minimum Bend Radius (mm)	6mm
Capacitance (pF/m)	95
Velocity of Propagation	70%
Shielding Effectiveness	<-120dB @ 1GHz



P/N: FR710-24MG3PF-XXX

2.4mm Male to G3PO (SMPS) Female Cable Assembly | .086" Semi-Rigid GUT-085 (Copper) Coax Cable | DC - 50GHz

Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC-50GHz	12dB to 50GHz	1.32 to 40GHz
200	±3			1.94 to 40GHz
300	±5			2.56 to 40GHz
500	±5			3.82 to 40GHz
1000	±10			6.92 to 40GHz

Environmental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-45 °C to +85 °C