


P/N: FR711-24MMMPXF-XXX

2.4mm Male to MMPX Female Cable Assembly | .086" Semi-Flexible Coax Cable Without FEP Jacket | DC - 50GHz



Dimensions are in mm




Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.4mm	MMPX
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Beryllium Copper
Connector Body Plating	Passivated	Gold

Cable Configuration

Cable Type	.086" Semi-Flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	Solid extruded PTFE
Number of Shields	1
Shield Layer 1 Material	Tin Plated Copper
Cable Diameter (mm)	2.2
Cable Color	Silver
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	< -110dB @ 1GHz



P/N: FR711-24MMMPXF-XXX

2.4mm Male to MMPX Female Cable Assembly | .086" Semi-Flexible Coax Cable Without FEP Jacket | DC - 50GHz

Electrical Data

Electrical Specifications for Different Length		
Length (mm)	Length Tolerance (mm)	Insertion Loss ≤ (dB)
100	±3	1.32 to 40GHz
150	±3	1.63 to 40GHz
200	±3	1.94 to 40GHz
250	±3	2.25 to 40GHz
300	±5	2.56 to 40GHz
400	±5	3.18 to 40GHz
500	±5	3.82 to 40GHz

Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-40°C to +125°C