


2.92mm Male to GPPO Female with Right Angle Cable Using .086" Semi-flexible Coax Without Jacket | DC - 40GHz **P/N: GA711-292MGPPWF-XXX**



Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.92mm	GPPO(Mini-SMP)
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Mount Method	None	None
Connector Body Style	Straight	Right Angle
Connector Body Material	Stainless Steel	Beryllium Copper
Connector Body Plating	Passivated	Gold

Cable Configuration

Cable Type	.086" Semi-Flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	Solid extruded PTFE
Number of Shields	1
Shield Layer 1 Material	Tin Plated Copper
Cable Diameter (mm)	2.2mm
Cable Color	Silver
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	> -110dB @ 1GHz

2.92mm Male to GPPO Female with Right Angle Cable Using .086" P/N: GA711-292MGPPWF-XXX
Semi-flexible Coax Without Jacket | DC - 40GHz


Electrical Data

Electrical Specifications for Different Length			
Length (mm)	Length Tolerance (mm)	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	12dB to 40GHz	1.32 to 40GHz
150	±3		1.63 to 40GHz
200	±3		1.94 to 40GHz
250	±3		2.25 to 40GHz
300	±5		2.56 to 40GHz
400	±5		3.21 to 40GHz
500	±5		3.82 to 40GHz


Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-55 °C to +165 °C
MIL/STD	N/A

Test Report for Cable assembly



*Note: Test Cable Assembly Length = 152 mm



*Note: Test Cable Assembly Length = 500 mm