


P/N: GA712-24M24M-XXX

2.4mm Male to 2.4mm Male Cable Assembly | 086" Semi-Flexible Coax Cable with FEP Jacket | DC - 50GHz




Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.4mm	2.4mm
Connector Polarity	Standard	Standard
Connector Gender	Male	Male
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Stainless Steel
Connector Body Plating	Passivated	Passivated

Cable Configuration

Cable Type	.086" Semi-Flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	Solid extruded PTFE
Shield Layer 1 Material	Tin Plated Copper
Jacket Material	FEP
Cable Diameter (mm)	2.54
Cable Color	Blue
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	< -110dB @ 1GHz



P/N: GA712-24M24M-XXX

2.4mm Male to 2.4mm Male Cable Assembly | 086" Semi-Flexible Coax Cable with FEP Jacket | DC - 50GHz

Electrical Data

Electrical Specifications for Different Length

Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss \leq (dB)
100	± 3	DC - 50GHz	1.40 to 50GHz	1.40 to 50GHz
150	± 3			1.75 to 50GHz
200	± 3			2.10 to 50GHz
250	± 3			2.45 to 50GHz
300	± 5			2.80 to 50GHz
400	± 5			3.45 to 50GHz
500	± 5			4.10 to 50GHz

Environmental Specifications


RoHS Compliant

Yes


Operating Temperature Range

-40°C to +125°C

Test Report for Cable assembly



*Note: Test Cable Assembly Length = 500 mm



*Note: Test Cable Assembly Length = 600 mm