


2.92mm Female to GPO (SMP) Female Cable Using .086" Semi-flexible Coax with FEP Jacket, DC - 40GHz

P/N: FR712-292FGPF-XXX



Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.92mm	GPO(SMP)
Connector Polarity	Standard	Standard
Connector Gender	Female	Female
Connector Impedance (Ohm)	50	50
Connector Mount Method	None	None
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Beryllium Copper
Connector Body Plating	Passivated	Gold

Cable Configuration

Cable Type	.086" Semi-Flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	Solid extruded PTFE
Number of Shields	1
Shield Layer 1 Material	Tin Plated Copper
Jacket Material	FEP
Jacket Diameter (mm)	2.54
Cable Color	Blue
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	> -110dB @ 1GHz

2.92mm Female to GPO (SMP) Female Cable Using .086" Semi-flexible Coax with FEP Jacket, DC - 40GHz

P/N: FR712-292FGPF-XXX

Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC-40GHz	14dB to 40GHz	14dB to 40GHz
150	±3			14dB to 40GHz
200	±3			14dB to 40GHz
250	±3			14dB to 40GHz
300	±5			14dB to 40GHz
400	±5			14dB to 40GHz
500	±5			14dB to 40GHz

Environmental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-40 °C to +80 °C
MIL/STD	N/A