


P/N: FR712-GPFGPWF-XXX

GPO(SMP) Femalee to GPO(SMP) Right Angle Female Cable Assembly | .086" Semi-Flexible Coax Cable With FEP Jacket | DC - 18GHz



Dimensions are in mm




## Connectors Configuration

	Connector 1	Connector 2
Connector Series	GPO(SMP)	GPO(SMP)
Connector Polarity	Standard	Standard
Connector Gender	Female	Female
Connector Impedance (Ohm)	50.0	50.0
Connector Body Style	Straight	Right Angle
Connector Body Material	CuBe	CuBe
Connector Body Plating	Gold	Gold

## Cable Configuration

Cable Type	.086" Semi-Flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	Solid extruded PTFE
Shield Layer 1 Material	Tin Plated Copper
Jacket Material	FEP
Cable Diameter (mm)	2.54
Cable Color	Blue
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	< -110dB @ 1GHz



## Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss $\leq$ (dB)
100	$\pm 3$	DC - 18GHz	1.35	0.83
200	$\pm 3$			1.16
300	$\pm 5$			1.49
500	$\pm 5$			2.15
1000	$\pm 10$			3.65

## Environmental Specifications


RoHS Compliant

Yes


Operating Temperature Range

-40°C to +165°C

## Test Report for Cable assembly



\*Note: Test Cable Assembly Length = 80 mm



\*Note: Test Cable Assembly Length = 330 mm

## Revision History

Version	Description	Prepared By	Approved By	Date
V1.0	Initial release	Grimm	Hebe	2024-01-01