


P/N: GA721-SMWMSMWM-XXX-18G

SMA Right Angle Male to SMA Right Angle Male Cable Assembly | .141" Semi-flexible Cable without Jacket □ DC-18GHz



Connectors Configuration

	Connector 1	Connector 2
Connector Series	SMA	SMA
Connector Polarity	Standard	Standard
Connector Gender	Male	Male
Connector Impedance (Ohm)	50	50
Connector Body Style	Right Angle	Right Angle
Connector Body Material	Stainless Steel	Stainless Steel
Connector Body Plating	Passivated	Passivated

Cable Configuration

Cable Type	Semi-flexible
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Covered Steel (SCCS)
Dielectric Material	PTFE
Number of Shields	1
Shield Layer 1 Material	Tin-soaked, Tin Plated Copper (T)
Cable Diameter (mm)	3.6
Cable Color	Silver
Minimum Bend Radius (mm)	10
Capacitance (pF/m)	94
Velocity of Propagation	71%
Shielding Effectiveness	>100dB



P/N: GA721-SMWMSMWM-XXX-18G

SMA Right Angle Male to SMA Right Angle Male Cable Assembly | .141" Semi-flexible Cable without Jacket □ DC-18GHz


Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC-18GHz	1.3	0.59
200	±3			0.79
300	±5			0.99
400	±5			1.19
500	±5	DC-18GHz		1.38


Environmental Specifications

RoHS Compliant
Yes
Operating Temperature Range
-40°C to +125°C

Test Report for Cable assembly



*Note: Test Cable Assembly Length = 400 mm



*Note: Test Cable Assembly Length = 600 mm