


P/N: FRF71-185MG3PF-XXX

## 1.85mm Male to G3PO(SMPS) Female Cable Assembly | RG-405SS Flexible Coax Cable | DC - 67GHz




### Connectors Configuration

	Connector 1	Connector 2
Connector Series	1.85mm	G3PO(SMPS)
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Beryllium Copper
Connector Body Plating	Passivated	Gold

### Cable Configuration

Cable Type	RG-405SS
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Wire
Dielectric Material	PTFE
Number of Shields	2
Shield Layer 1 Material	Silver Plated Copper Tape
Shield Layer 2 Material	Silver Plated Copper Braid
Jacket Material	FEP
Cable Diameter (mm)	2.64
Cable Color	Turquoise
Minimum Bend Radius (mm)	6
Capacitance (pF/m)	96.5
Velocity of Propagation	70%
Shielding Effectiveness	< -100dB @ 1GHz



P/N: FRF71-185MG3PF-XXX

1.85mm Male to G3PO(SMPS) Female Cable Assembly | RG-405SS Flexible Coax Cable | DC - 67GHz

## Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC - 67GHz	10dB to 67GHz	1.79 to 67GHz
200	±3			2.55 to 67GHz
300	±5			3.32 to 67GHz
500	±5			4.85 to 67GHz
800	±10			7.18 to 67GHz
1000	±10			8.65 to 67GHz
1500	±15			12.45 to 67GHz
2000	±20			16.20 to 67GHz

## Environmental Specifications


RoHS Compliant

Yes


Operating Temperature Range

-45°C to +125°C

## Test Report for Cable assembly



\*Note: Test Cable Assembly Length = 200 mm



\*Note: Test Cable Assembly Length = 300 mm