


P/N: FRR1P-SMMSMYF-XXX

SMA Male to SMA Bulkhead Female Cable Assembly | RG142-PVC Flexible Coax Cable | DC-6GHz




## Connectors Configuration

	Connector 1	Connector 2
Connector Series	SMA	SMA
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Mount Method	None	Bulkhead
Connector Body Style	Straight	Straight
Connector Body Material	Brass	Brass
Connector Body Plating	Tri-Metal	Gold

## Cable Configuration

Cable Type	RG142-PVC Flexible Cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper
Dielectric Material	PTFE
Shield Layer 1 Material	silver plated copper braid
Shield Layer 2 Material	silver plated copper braid
Jacket Material	PVC
Cable Diameter (mm)	5.25±0.1
Cable Color	Blue
Minimum Bend Radius (mm)	25
Capacitance (pF/m)	96.45
Velocity of Propagation	70%
Shielding Effectiveness	< -80dB @ 1GHz




## Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss $\leq$ (dB)
100	$\pm 3$	DC - 6GHz	1.25	0.62
200	$\pm 3$			0.75
500	$\pm 5$			1.14
1000	$\pm 10$			1.79
2000	$\pm 20$			3.09
3000	$\pm 30$			4.39

## Environmental Specifications

RoHS Compliant Yes  
 Operating Temperature Range -20°C to +70°C

## Test Report for Cable assembly



\*Note: Test Cable Assembly Length = 100 mm

## Revision History

Version	Description	Prepared By	Approved By	Date