


## P/N: FRR1P-SMWMSMWM-XXX

### SMA Right Angle Male to SMA Right Angle Male Cable Assembly | RG142-PVC Flexible Coax Cable | DC-6GHz




## Connectors Configuration

	Connector 1	Connector 2
Connector Series	SMA	SMA
Connector Polarity	Standard	Standard
Connector Gender	Male	Male
Connector Impedance (Ohm)	50	50
Connector Body Style	Right Angle	Right Angle
Connector Body Material	Brass	Brass
Connector Body Plating	Nickel	Nickel

## Cable Configuration

Cable Type	RG142-PVC Flexible Cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper
Dielectric Material	PTFE
Shield Layer 1 Material	silver plated copper braid
Shield Layer 2 Material	silver plated copper braid
Jacket Material	PVC
Cable Diameter (mm)	5.25±0.1
Cable Color	Blue
Minimum Bend Radius (mm)	25
Capacitance (pF/m)	96.45
Velocity of Propagation	70%
Shielding Effectiveness	< -80dB @ 1GHz



## Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC - 6GHz	1.4	0.82
200	±3			0.95
500	±5			1.34
1000	±10			1.99
2000	±20			3.29
3000	±30			4.59

## Environmental Specifications

RoHS Compliant

Yes

Operating Temperature Range

-20°C to +70°C

## Revision History

Version	Description	Prepared By	Approved By	Date