

TNC Male to TNC Female Reverse Polarity, Cable Using .RG223 Series Coax with FEP Jacket, DC - 3GHz

P/N: FRR2-TNCFMRPTNCF-XXX



Connectors Configuration

	Connector 1	Connector 2
Connector Series	TNC	TNC
Connector Polarity	Standard	Reverse Polarity
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Mount Method	None	None
Connector Body Style	Straight	Straight
Connector Body Material	Brass	Brass
Connector Body Plating	Nickel	Nickel

Cable Configuration

Cable Type	RG223
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Wire
Dielectric Material	Solide PE
Number of Shields	2
Shield Layer 1 Material	Silver Plated Copper Braid
Shield Layer 2 Material	Silver Plated Copper Braid
Jacket Material	PVC, Black
Jacket Diameter (mm)	5.4
Cable Color	Black
Minimum Bend Radius (mm)	25
Capacitance (pF/m)	101.05
Velocity of Propagation	66
Shielding Effectiveness	<-80dB @ 1GHz

TNC Male to TNC Female Reverse Polarity, Cable Using .RG223 P/N: FRR2-TNCF-XXX
 Series Coax with FEP Jacket, DC - 3GHz

Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
500	±5	DC to 6GHz	1.50 to 6GHz	1.05 to 6GHz
800	±10			1.55 to 6GHz
1000	±10			1.95 to 6GHz
1500	±15			2.85 to 6GHz
2000	±20			3.65 to 6GHz
3000	±30			5.55 to 6GHz
5000	±50			9.1 to 6GHz

Environmental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-55 °C to +85 °C
MIL/STD	N/A