Flexi RF
Reliable RF Components In Stock

Datasheet

P/N: FRR8-SMMSSMBF-XXX

SMA Male to SSMB Female Cable Assembly | RG178 Flexible Coax Cable | DC - 3GHz



Connectors Configuration

	Connector 1	Connector 2
Connector Series	SMA	SSMB
Connector Polarity	Standard	Standard
Connector Gender	Male	Female
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Brass	Brass
Connector Body Plating	Gold	Gold

Cable Configuration

Cable Type	RG178
Cable Impedance (Ohm)	50
Inner Conductor Material	Copper Clad Steel, Silver,7 Strands
Dielectric Material	PTFE
Number of Shields	1
Shield Layer 1 Material	Silver Plated Copper Braid
Jacket Material	FEP
Cable Diameter (mm)	1.83
Cable Color	tan
Minimum Bend Radius (mm)	10.16
Capacitance (pF/m)	96.5
Velocity of Propagation	70%
Shielding Effectiveness	>-70dB@1GHz



Flexi RF Inc
(650)880-9199
20045 Stevens Creek Blvd., Suite 2B, Cupertino, CA 95014
sales@flexirf.com
www.flexirf.com

P/N: FRR8-SMMSSMBF-XXX

SMA Male to SSMB Female Cable Assembly | RG178 Flexible Coax Cable | DC - 3GHz

Electrical Data

Electrical Specifications for Different Length

Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
500	±5	DC - 6GHz	1.30 to 3GHz	1.75 to 3GHz
800	±10			2.44 to 3GHz
1000	±10			2.95 to 3GHz
1500	±15			4.15 to 3GHz
2000	±20			5.35 to 3GHz
3000	±30	DC - 6GHz		7.65 to 3GHz
5000	±50			12.25 to 3GHz

Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-40 ºC to +80 ºC
MIL/STD	N/A

Test Report for Cable assembly



*Note:Test Cable Assembly Length = 230 mm



*Note:Test Cable Assembly Length = 1000 mm