


P/N: FRU2-24M24M-XXX

## 2.4mm Male to 2.4mm Male Cable Assembly | 3506 Series Low Loss Phase Stable Flexible Coax Cable | DC - 50GHz




### Connectors Configuration

	Connector 1	Connector 2
Connector Series	2.4mm	2.4mm
Connector Polarity	Standard	Standard
Connector Gender	Male	Male
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Stainless Steel
Connector Body Plating	Passivated	Passivated

### Cable Configuration

Cable Type	GT3506 flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Wire
Dielectric Material	LD-PTFE
Number of Shields	2
Shield Layer 1 Material	Silver Plated Copper Tape
Shield Layer 2 Material	Silver Plated Copper Braid
Jacket Material	FEP
Cable Diameter (mm)	2.2
Cable Color	Gray
Minimum Bend Radius (mm)	11
Capacitance (pF/m)	94
Velocity of Propagation	82%
Shielding Effectiveness	< -100dB @ 1GHz



## Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss $\leq$ (dB)
100	$\pm 3$	DC - 50GHz	1.44 to 50GHz	1.15 to 50GHz
200	$\pm 3$			1.45 to 50GHz
300	$\pm 5$			2.1 to 50GHz
500	$\pm 5$			3.32 to 50GHz
800	$\pm 10$			5.0 to 50GHz
1000	$\pm 10$			5.78 to 50GHz
1500	$\pm 15$			8.53 to 50GHz
2000	$\pm 20$			10.94 to 50GHz

## Environmental Specifications


RoHS Compliant

Yes


Operating Temperature Range

-55 °C to +125 °C

## Test Report for Cable assembly



\*Note: Test Cable Assembly Length = 370 mm



\*Note: Test Cable Assembly Length = 1000 mm

## Revision History

Version	Description	Prepared By	Approved By	Date
V1.0	Initial release	Grimm	Hebe	2024-01-01