


P/N: GAU2-SMMSMM-XXX

SMA Male to SMA Male Cable Assembly | 3506 Series Low Loss Phase Stable Flexible Coax Cable | DC - 26.5GHz



Connectors Configuration

	Connector 1	Connector 2
Connector Series	SMA	SMA
Connector Polarity	Standard	Standard
Connector Gender	Male	Male
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Stainless Steel
Connector Body Plating	Passivated	Passivated

Cable Configuration

Cable Type	GT3506 flexible cable
Cable Impedance (Ohm)	50
Inner Conductor Material	Silver Plated Copper Wire
Dielectric Material	LD-PTFE
Number of Shields	2
Shield Layer 1 Material	Silver Plated Copper Tape
Shield Layer 2 Material	Silver Plated Copper Braid
Jacket Material	FEP
Cable Diameter (mm)	2.2
Cable Color	Gray
Minimum Bend Radius (mm)	11
Capacitance (pF/m)	94
Velocity of Propagation	82%
Shielding Effectiveness	< -100dB @ 1GHz



P/N: GAU2-SMMSMM-XXX

SMA Male to SMA Male Cable Assembly | 3506 Series Low Loss Phase Stable Flexible Coax Cable | DC - 26.5GHz


Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
100	±3	DC - 18GHz	1.25 to 18GHz	0.75 to 18GHz
200	±3			1.06 to 18GHz
300	±5			1.36 to 18GHz
500	±5			1.94 to 18GHz
800	±10			2.83 to 18GHz
1000	±10			3.35 to 18GHz
1500	±15			4.76 to 18GHz
2000	±20			6.20 to 18GHz


Environmental Specifications

RoHS Compliant
Yes
Operating Temperature Range
-55 °C to +125 °C

Test Report for Cable assembly



*Note: Test Cable Assembly Length = 200 mm



*Note: Test Cable Assembly Length = 500 mm