




## **Broadband Waveguide Horn Antenna Operating from 1 GHz to 18 GHz with a Nominal 11 dBi Gain | N Female Input Connector**



Dimensions are in mm

## Product Configuration

Connector Series	N
Connector Polarity	Standard
Connector Gender	Female
Connector Impedance (Ohm)	50
Antenna Type	Horn

## Mechanical Data

Weight	1,429 g
Body Material	Aluminum
Colour	Silver

## Electrical Specifications

Power, Max Input (Watts)	50
Return Loss or VSWR Input	2.5
Directionality	Directional
Polarization	Linear
Number of Bands	Single
Gain, Typical (dBi)	11

## Environmental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-40 °C to +80 °C




**Flexi RF**  
Reliable RF Components In Stock

**Datasheet**

**Broadband Waveguide Horn Antenna Operating from 1 GHz to 18 GHz with a Nominal 11 dBi Gain | N Female Input Connector**

**P/N: GHA0118A-11**


### VSWR Test Figure



### Bandwidth & Gain Table

Frequency (GHz)	E Beamwidth (°)	H Beamwidth (°)	Gain (dBi)
1.0	91.0	68.7	5.2
1.5	66.8	59.8	9.4
2.0	49.4	56.8	9.4
2.5	40.3	60.4	9.8
3.0	38.9	61.0	9.9
3.5	36.8	61.4	10.0
4.0	37.5	62.6	10.5
4.5	34.1	46.5	11.3
5.0	51.5	43.0	11.7
5.5	47.5	40.2	11.8
6.0	43.4	36.9	12.3
6.5	41.4	29.0	12.7
7.0	46.5	28.2	12.5
7.5	51.0	33.6	11.8
8.0	44.8	33.5	11.8
8.5	45.2	33.8	12.0
9.0	47.4	33.0	11.8
9.5	46.2	34.8	12.4
10.0	45.3	32.5	13.2
10.5	45.8	30.9	13.3
11.0	45.3	33.0	13.1
11.5	48.1	32.6	12.8
12.0	50.5	32.9	12.5
12.5	46.6	35.4	13.1
13.0	41.7	36.5	12.1
13.5	37.0	34.6	11.2
14.0	17.0	33.4	11.4
14.5	17.9	33.4	11.0
15.0	45.4	30.8	12.1
15.5	15.8	9.9	14.6
16.0	10.7	6.8	16.0
16.5	9.7	8.1	15.6
17.0	8.9	12.1	14.9
17.5	8.7	16.6	12.6
18.0	38.5	7.7	9.1

### Bandwidth & Gain Test Figures



**Flexi RF Inc**

**(650)880-9199**

**20045 Stevens Creek Blvd., Suite 2B, Cupertino, CA 95014**

**sales@flexirf.com**

**www.flexirf.com**

**Page 2**