Flexi RF
Reliable RF Components In Stock

Datasheet

Isolator with 16dB Isolation from 2GHz to 6GHz | 20 Watts with SMA Female

P/N: GIS020060-SMF





Product Configuration

Connector-In Series	SMA
Connector-In Polarity	Standard
Connector-In Gender	Female
Connector-In Impedance (Ohm)	50
Connector-Out Series	SMA
Connector-Out Polarity	Standard
Connector-Out Gender	Female
Connector-Out Impedance (Ohm)	50

Mechanical Data

Weight (g)	66
Body Material	Aluminum
Body Plating	Oxidation
Connector In Body Material	Brass
Connector In Body Plating	Gold
Connector Out Body Material	Brass
Connector Out Body Plating	Gold
External body material	Nickel plated iron

Flexi RF Inc
(650)880-9199
20195 Stevens Creek Blvd, Suite 220, Cupertino, CA 95014
sales@flexirf.com
www.flexirf.com

Isolator with 16dB Isolation from 2GHz to 6GHz | 20 Watts with SMA Female

P/N: GIS020060-SMF

Electrical Specifications

VSWR / Return Loss	≤1.40
Insertion Loss	≤ 0.7dB
Power, Max Input (Watts)	20
Frequency Range	2GHz~6GHz
Isolation Min.(dB)	16

Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	0°C to +60 ºC
Storage Temperature Range	-40 ºC to +85 ºC

Test Data

