


**Isolator with 13.8dB Isolation from 26.5GHz to 40GHz | 5Watts with 2.92mm Female**

**P/N: GIS265400-292F**



Dimensions are in mm



## Product Configuration

Connector-In Series	2.92mm
Connector-In Polarity	Standard
Connector-In Gender	Female
Connector-In Impedance (Ohm)	50
Connector-Out Series	2.92mm
Connector-Out Polarity	Standard
Connector-Out Gender	Female
Connector-Out Impedance (Ohm)	50

## Mechanical Data

Weight (g)	31
Body Material	Aluminum
Body Plating	Oxidation
Connector In Body Material	Stainless Steel
Connector In Body Plating	Passivated
Connector Out Body Material	Stainless Steel
Connector Out Body Plating	Passivated
External body material	Nickel plated iron

**Isolator with 13.8dB Isolation from 26.5GHz to 40GHz | 5Watts with 2.92mm Female**

**P/N: GIS265400-292F**

**Electrical Specifications**

VSWR / Return Loss	≤1.65
Insertion Loss	≤ 1.4dB
Power, Max Input (Watts)	5
Frequency Range	26.5GHz~40GHz
Isolation Min.(dB)	13.8

**Environmental Specifications**

RoHS Compliant	Yes
Operating Temperature Range	-40°C+85°C
Storage Temperature Range	-55 °C to +85 °C

**Test Data**

