
Flexi RF
Reliable RF Components In Stock

Datasheet

SMA Female Low Noise Amplifier (LNA) | 40dB Gain | 2.5dB Noise Figure | 800MHz - 18GHz

P/N: GWLNA008018-40



Dimensions are in mm



Product Configuration

Connector-In Series	SMA
Connector-In Polarity	Standard
Connector-In Gender	Female
Connector-In Impedance (Ohm)	50
Connector-Out Series	SMA
Connector-Out Polarity	Standard
Connector-Out Gender	Female
Connector-Out Impedance (Ohm)	50

Electrical Specifications

Frequency Range	800MHz to 18GHz
Return Loss or VSWR Input	1.8
Return Loss or VSWR Output	2.2
Gain, Typical (dB)	40
Gain Flatness (dB)	±2.0
P-1dB (dBm)	13
Noise Figure, Max (dB)	3.0
3rd Intercept Point (dB)	25
Voltage, DC Typ (Volts)	+12
Voltage, DC Max (Volts)	+12
Current, Max (mA)	150
Max Input Power (dBm)	0

Flexi RF Inc

(650)880-9199
20195 Stevens Creek Blvd, Suite 220, Cupertino, CA 95014
sales@flexirf.com
www.flexirf.com

SMA Female Low Noise Amplifier (LNA) | 40dB Gain | 2.5dB Noise Figure | 800MHz - 18GHz

P/N: GWLNA008018-40

Mechanical Data

Min. Mating Cycles	≥500
Body Material	Brass
Body Plating	Nickel

Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	-40 ºC to +70 ºC
Storage Temperature Range	-40 ºC to +85 ºC