

SMA Male to GPO (SMP) Male Adapter, DC - 18GHz**FR1-SMA/GPO-JJS****Product Configuration**

| | |
|-----------------------------|----------|
| Connector 1 Series | SMA |
| Connector 1 Polarity | Standard |
| Connector 1 Gender | Male |
| Connector 1 Impedance (Ohm) | 50 |
| Connector 1 Mount Method | None |
| Connector 2 Series | GPO(SMP) |
| Connector 2 Polarity | Standard |
| Connector 2 Gender | Male |
| Connector 2 Impedance (Ohm) | 50 |
| Connector 2 Mount Method | None |
| Body Style | Straight |

Mechanical Data

| | |
|---------------------------|-----------------|
| Connector 1 Body Material | Stainless Steel |
| Connector 1 Body Plating | Passivated |
| Connector 2 Body Material | Stainless Steel |
| Connector 2 Body Plating | Passivated |
| Min. Mating Cycles | ≥500 |

Electrical Specifications

| | |
|-----------|-------------|
| Frequency | DC to 18GHz |
| VSWR | 1.50 |

Environmental Specifications

| | |
|-----------------------------|-------------------|
| RoHS Compliant | Yes |
| Operating Temperature Range | -55 °C to +165 °C |
| MIL/STD | N/A |