
Flexi RF
Reliable RF Components In Stock

Datasheet

P/N: VNA-NMD35F35F-XXX

3.5mm NMD Female to 3.5mm Female Cable Assembly | Precision Flexible VNA Test Cable | With Armor | DC - 26.5GHz



Dimensions are in mm



Connectors Configuration

	Connector 1	Connector 2
Connector Series	3.5mm NMD	3.5mm
Connector Polarity	Standard	Standard
Connector Gender	Female	Female
Connector Impedance (Ohm)	50	50
Connector Body Style	Straight	Straight
Connector Body Material	Stainless Steel	Stainless Steel
Connector Body Plating	Passivated	Passivated

Cable Configuration

Cable Impedance (Ohm)	50
Cable Diameter (mm)	15.2
Minimum Bend Radius (mm)	50
Shielding Effectiveness	>100dB to 18GHz

Flexi RF Inc
(650)880-9199
20195 Stevens Creek Blvd, Suite 220, Cupertino, CA 95014
sales@flexirf.com
www.flexirf.com

Electrical Data

Electrical Specifications for Different Length				
Length (mm)	Length Tolerance (mm)	Frequency	VSWR / Return Loss	Insertion Loss ≤ (dB)
1000	±10	DC-26.5GHz	1.25 to 26.5GHz	3.32
630	±5			2.38

Enviromental Specifications

RoHS Compliant	Yes
Operating Temperature Range	0 ºC to +40 ºC
MIL/STD	N/A

Revision History

Version	Description	Prepared By	Approved By	Date