



Description

Easyroll 125mm Central Dual Lock H7 Series Castor 120kg is designed for indoor applications and is built with a robust polypropylene housing and precision bearing assembly. It features a single raceway and utilises thermoplastic rubber for the wheel to provide dependable operational stability. The incorporation of bearing steel and a directional brake with a bolt-secured socket fitting ensures smooth control and reliable movement for trade professionals performing routine equipment handling.

Features

- Polypropylene housing ensures robust, durable castor construction
- Thermoplastic rubber wheel provides smooth noise reduced movement
- Precision bearing steel improves smooth rotation
- Socket fitting ensures secure straightforward installation
- Bolt attachment enhances overall castor stability
- Directional brake offers reliable controlled stopping power
- 125mm wheel core design provides balanced load distribution
- Dual lock mechanism improves overall castor safety during manoeuvres

Product Code: H75R35K125

Specifications

| | |
|--------------|-------------------|
| Outdoor Use | No |
| Indoor Use | Yes |
| Bearing Type | Precision Bearing |
| Raceway Type | Single |
| Brake Type | Directional |
| Fitting Type | Socket |

Appearance

| | |
|----------------|-------------------|
| Product Colour | Grey/Silver/White |
|----------------|-------------------|

Construction

| | |
|---------------------|----------------------|
| Wheel Core Material | Polypropylene |
| Wheel Material | Thermoplastic Rubber |
| Housing Material | Polypropylene |
| Bearing Material | Bearing Steel |

Dimensions

| | |
|-------------------------|------|
| Product Length mm | 502 |
| Product Width mm | 523 |
| Product Height mm | 259 |
| Wheel Diameter | 125 |
| Tread Width mm | 31.6 |
| Finish Height mm | 259 |
| Bolt Thread Length (mm) | 100 |
| Bolt Thread Width (mm) | 27.8 |
| Mounting Size (G) mm | M28 |