



Description

Easyroll 150mm Blue Rubber Fixed Plate J3 Series Castor 300kg offers a durable and well-engineered mobility solution designed with a plate mount for precise applications. It features a robust steel housing, a polypropylene wheel core, and reliable rubber wheels that ensure smooth movement and stability. Professionals benefit from its ball bearing design and total brake system, which allow for controlled manoeuvrability and dependable performance across various operational settings.

Features

- Heavy duty steel housing ensures solid structural integrity
- Polypropylene wheel core offers high resistance and stability
- Ball bearing design provides smooth and reliable rotation
- Rubber wheel permits optimal traction and vibration dampening
- Distinct red, black and silver accents aid visual identification
- Total brake system enables precise controlled stopping
- Single raceway design simplifies maintenance and installation
- Plate mount fitting ensures secure attachment to surfaces

Product Code: J33AZ83K150

Specifications

| | |
|--------------|--------------------------|
| Outdoor Use | Yes |
| Indoor Use | Yes |
| Bearing Type | Ball Bearing |
| Raceway Type | Single |
| Brake Type | Total |
| Attachments | Plate Swivel Total Brake |

Appearance

| | |
|----------------|------------------|
| Product Colour | Red/Black/Silver |
|----------------|------------------|

Construction

| | |
|---------------------|---------------|
| Wheel Core Material | Polypropylene |
| Wheel Material | Steel |
| Housing Material | Steel |
| Bearing Material | Carbon Steel |

Weights

| | |
|------------------------|-------|
| Product Weight (grams) | 2125 |
| Product Weight (kg) | 2.125 |
| Load Capacity kg | 300.0 |

Dimensions

| | |
|-----------------------------|---------|
| Product Length mm | 150 |
| Product Width mm | 110 |
| Product Height mm | 191 |
| Wheel Diameter | 150 |
| Tread Width mm | 43 |
| Mounting Hole Dimensions mm | 17x11 |
| Hole Centre Dimensions mm | 105x80 |
| Plate Dimensions mm | 135x110 |