

# DUAL SPRAY FAUCET KIT / LINEAR

**ACTION: FAUCET KIT** 

KNURL: LINEAR

RANGE: KITCHEN FAUCETS

An upgrade kit that adds a dual-spray function to your existing Buster + Punch faucet with pull-out, letting you toggle between aerated or needle spray. For use with a Buster + Punch pull-out faucet. Features a pull-out nozzle with our signature linear knurling. Available in steel, gun metal and black finishes











.91"

### SPECIFICATIONS

A kitchen faucet with pull-out and dual spray function, mixing warm and cold, aerated water. The pull-out nozzle can be toggled between aerated or a needle spray. Needle spray covers a wider area than aerated spray. Maximum thickness of mounting surface 70mm, with supplied fixings. Minimum recommended water pressure: 7.25 PSI (0.5 BAR). Maximum recommended water pressure: 72 PSI (5 BAR). Recommended maximum hot water temperature: 70 °C (158°F). Recommended temperature range: 5 – 60 °C (41 – 140 °F). The total length of the pull-out hose is 66.9°. Note: Exceeding these temperatures or water pressures can result in damage to the tap. A pressure reducing valve may be required to be fitted in high water pressure situations.

### FINISH & SKU NUMBERS

sku:	finish:	size:
NKT-353252	gun metal	
NKT-073251	welders black	
NKT-593253	steel	

## CARE INSTRUCTIONS

Wipe with damp cloth with no loose hairs, avoid using any chemicals. Please note all finishes are prone to aging.

#### INCLUDED

1 x Kitchen Faucet Dual Spray Kit

## PLEASE NOTE

All Buster + Punch mixer taps conform to standard EN817. In some cases, local housing regulations may require mixer taps to be of a higher minimum water pressure standard. In this instance we would recommend consulting with a certified plumber about installing a pressure regulator or similar device. Mixer taps are tested to work with a max. pressure of 10 bar (1000 kPa) and recommended working pressure range is 1.0 – 5.0 bar (1000 kPa – 500 kPa).