EU KITCHEN TAP / PULL-OUT MIXER / CROSS

ACTION: KITCHEN TAP WITH PULL OUT SPRAY

KNURL: CROSS

RANGE: KITCHEN TAPS

A kitchen tap with single lever mixer with pull out spray. This tap has been cast, sand- blasted and machined from solid metal in Italy. It features our signature cross-knurl pattern and is refined by hand.


Only available for sale to the following countries: Austria, Czech Republic, Denmark, France, Germany, Greece, Hungary, Iceland, Italy, Netherlands, Norway, Portugal, Romania, Serbia, Spain, Sweden and Switzerland.











SPECIFICATIONS

A kitchen mixer tap with pull out spray, with a single lever action that mixes water from the hot and cold pipes in your kitchen.
The mixer tap with pull out spray can be installed on a worktop with a maximum thickness of 70mm. There are no components available for fixing this tap on a worktop with a thickness of greater than 70mm.
Minimum recommended water pressure: 10.2 PSI (0.7 BAR).
Maximum recommended water pressure: 72 PSI (5 BAR).
Recommended maximum hot water temperature: 70 °C (158°F).
Recommended temperature range: 5 – 60 °C (41 – 140°F).
Pull out spray connection hose length: 1.7 m
Pull out spray extraction length: 45 cm (approx from end of mixer)
UK flexible connector hose diameter: 1/2" ø
EU flexible connector hose diameter: 3/8" ø
Cartridge material: ceramic
360 degree swivel spout.
Note: exceeding these temperatures or water pressures can result in damage to the tap. A pressure reducing valve may be required to be fitted in high water pressure situations.

FINISH & SKU NUMBERS

sku:	finish:	size:
C0-052622	brass	
C0-072621	steel	
C0-592623	welders black	

INCLUDED

1 x Kitchen Mixer Tap with Pull Out Spray
2 x Flexible connector hoses
1 x Tap Base and set of washers
1 x Threaded bar and nut
1 x Supporting tap brace (for surfaces with thickness <5mm)
[info. INSTALLATION TOOLS REQUIRED.]
1 x Adjustable spanner

PLEASE NOTE

All Buster + Punch mixer taps conform to standard EN817. In some cases, local housing regulations may require mixer taps to be of a higher minimum water pressure standard. In this instance we would recommend consulting with a certified plumber about installing a pressure regulator or similar device. Mixer taps are tested to work with a max. pressure of 10 bar (1000 kPa) and recommended working pressure range is 1.0 – 5.0 bar (100 kPa – 500 kPa).
Images shown are for illustration purposes only.

CARE INSTRUCTIONS

Wipe with lint free cloth with no loose hairs, avoid using any chemicals. Please note that finishes may age naturally with time and regular use.