

TOGGLE MODULE / INTERMEDIATE

ACTION: 3 WAY

RANGE: TOGGLE MODULE

An intermediate toggle module as used in the current toggle completes for the Australian and New Zealand region. Combine with Buster + Punch plates, detail kits and other modules to create your perfect switch.








17.2 mm

45 mm

23 mm



SPECIFICATIONS

Style: On/Off Intermediate Toggle Switch

Switching: 3 way Input: 220-250VAC

Load: 10AX

Compatibility: For use with Standard 1/2/3 Way Wiring

accessories.

Not compatible with Retractive Wiring + Dimmers. Please

consult user manual

For Use In: Australia & New Zealand Certification: SAA-221305-EA, AS 3133:2020 Testing Includes:

Endurance - 12,000 cycles @ 100% max load

Resistance to Heat - 125C

Dielectric Voltage Withstand - 2000V \updeta 3000V Not Suitable for Fans, Motors or any other type of large

inductive load.

FINISH & SKU NUMBERS

sku:	finish:	size:
GZTM-013292	black	N/A

CARE INSTRUCTIONS

Wipe with a dry lint free cloth with no loose hairs, avoid using any chemicals. Please note that finishes may age naturally with time and regular use.

INCLUDED

1 x Intermediate Toggle Module

PLEASE NOTE

DISCLAIMER: Always consult a trade professional when installing this product. Buster + Punch is not responsible for the usage or feasibility of installation requirements. This product is not suitable for damp or wet environments.