

# Safety Deck Hatch



Product Specification	
Colour	Red
Material	Frame – Powder Coated Mild Steel
	30mm x 30mm x 3mm angle; Checker
	Tread Plates – Powder Coated Mild
	Steel Plates 5 bar x 3mm thick; Hinges -
	Stainless Steel
Weight	10kg

## Range

Size
Total length 1300mm, letterbox section
1050mm x 90mm with access hatch
250mm x 250mm

The adapted version of our versatile plasterboard hatch now features an additional access hatch, designed for easy transfer of platform deck panels and leg units between floors.

The Safety Deck Hatch can remain in place until pre-painting, allowing for the safe passage of other essential components, such as architraves, skirting boards, and pipework.

This product is ideal for both residential and commercial environments, providing a practical solution for efficient movement of materials during construction and renovation projects.

### **Features & Benefits**

- Safe and efficient way of transporting large format sheets, platform deck panels and leg units between floors safely
- Anti-slip checker lid
- · Heavy duty steel construction for durability and safety
- Reusable from plot to plot and site to site
- · Reduces traffic on busy stairways to promote safe working practices

### Installation Instructions/Guidelines

- Prior to installation, please ensure there is sufficient support to all sides of the opening before installation.
- Measure out and create the opening in the floor. Check the product sizes on site prior to cutting any opening as sizes may vary.
- The product frame should be fixed using all of the screw holes on the product.
- All screws should be a minimum of 4mm (8G) x 45mm chipboard screws.
- · Always leave the checker lid closed when not in use.















#### **Product Disclaimer**

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Safety Deck Hatch 17 September 2025



0800 834 704 | 01625 855600 enquiries@protection.co.uk www.protection.co.uk

