

# Anisotropic Magnet

## Product Specification

|                       |  |
|-----------------------|--|
| Adhesive              | 130 microns including carrier  |
| Colour                | Dark brown   |
| Density               | 3.6g/cm3   |
| Material              | 90% high grade anisotropic ferrite powder, 10% synthetic binder, free of PVC & phthalates. |
| Operating Temperature | -10°C to 60°C above which performance will reduce.   |
| Thickness             | 1.5mm  |
| Width                 | 100mm x 100mm  |

## Installation Instructions/Guidelines

- Surface preparation is crucial when applying this adhesive.
- Alcohol wipes are recommended as surface cleansers.
- After that, apply the product with even pressure & allow 12 hours to elapse before applying any load.

## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Anisotropic Magnet 13 December 2025



0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

