

# Ultra Low Tack Tape



## Product Specification

Adhesive	Rubber
Colour	Black
Density	0.93g/cm <sup>3</sup>
Material	LDPE Protection Film
Thickness	0.08mm ± 0.005mm
Weight Per Roll	0.45kg

## Range

Code	Size
BLACKULTRALOWTAC	50mm x 100m

## Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test suitability
- Please contact our technical department for specific advice

## Handling & Storage

- Store in ambient conditions. Please note the performance of tape varies in extreme temperatures, subzero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the tape is removed.

**Our Ultra Low Tack Tape is the ideal solution for masking off surfaces with high gloss or powder-coated finishes. It features a unique adhesive that ensures no leftover residue after removal, making it perfect for both home and commercial applications.**

**Always test your tape before applying to highly finished surfaces. For veneer doors, we recommend using a high-quality protective Door Sleeve instead.**

## Features & Benefits

- Masks off sensitive surfaces without leaving residue.
- Ultra Low Tack Tape designed for high gloss and powder coated finishes.
- Recommended to test on surfaces before full application.
- Syntha Pulvin Approved Tape.
- 50mm x 100m Roll

## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Ultra Low Tack Tape 25 January 2026



0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

