

# Carpetshield®FR



## Features & Benefits

- Reverse wound, enabling quick and easy installation
- Lightweight for ease of handling around site
- Requires no taping, saving time
- Low tack adhesive to avoid any residue being left behind after removal

## Product Specification

Adhesive	Acrylic Solvent Adhesive
Colour	White with markings
Thickness	80 micron
Weight Per Roll	600mm x 100m - 4kg, 800mm x 100m - 5.5kg, 900mm x 100m - 6kg, 1200mm x 100m - 7kg

## Range

Code	Size
CARPETSHIELD1200	1200mm x 100m
CARPETSHIELD600	600mm x 100m
CARPETSHIELD800	800mm x 100m
CARPETSHIELD900	900mm x 100m

## Installation Instructions/Guidelines

- Refer to full guidelines issued with the product prior to installation and check suitability
- Clear all debris from the carpet prior to installation
- Simply roll out the reverse wound product
- Apply pressure to the film on to the carpet to activate the adhesive
- Where carpet has been installed using a glue or adhesive, do not install for at least 72 hours so that the adhesive vapours can dissipate before application.
- Do not apply to damp carpet or in areas that may be subject to moisture accumulation
- Excessive traffic and exposure to direct sunlight or intense heat may accelerate adhesive transfer.

## Handling & Storage

- Store and install in ambient conditions. The rolls should be stored at room temperature 24 hours prior to installation.

## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Carpetshield®FR 07 December 2025



0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

