

CavityStep



Product Specification

Colour	Powder coated Yellow
Material	3mm Aluminium 5 bar plate
Width	740mm
Weight	5kg

Range

Code	Size
CAVITYSTEP	740mm

Installation Instructions/Guidelines

- Used to bridge the cavity wall by creating a safer platform, reducing the risks of site personnel slipping or tripping.
- After joists are fixed and the first decking platform is laid, the Cavity Step can be fixed into the joists through the decking, allowing safe access to the floor deck.

Handling & Storage

- Store in ambient conditions.

Features & Benefits

- Safe walkway over cavity walls under construction
- Bridges the cavity for easy access to working deck from scaffolding
- Reusable across different plots and sites
- Easy installation and removal
- Anti-slip profile to minimize risk of trips or falls

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: CavityStep 20 August 2025

