

# Crossweave High Tack Tape



## Features & Benefits

- Extra Heavy duty PET tape for use with heavier grade Proplex & Impactboard
- Tear resistant and reinforced crossweave design
- High tensile Strength & High Abrasion 1 Resistance

## Applications

Reinforcing carton sealing, bundling, splicing and palletizing

## Product Specification

Application Temperature	26-66°C
Elongation at Break	5%
Material	Crossweave fiberglass filament reinforced clear PET, coated with a synthetic rubber and hydrocarbon resin adhesive
Operating Temperature	10-40°C
Tensile Strength	150 lbs/in
Thickness	170 mic
Water Resistant	Yes

## Range

Code	Size
CROSSWEAVETAPE75	75mm x 50m

## Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test the suitability
- We do not recommend applying any tape to veneer surfaces
- Please contact our technical department for specific advice
- Ensure the surface is as clean as possible before applying the tape to create the strongest seal
- Inspect the tape at regular intervals to assess the level of adhesion

## Handling & Storage

- Store in ambient conditions.

Please note the performance of tape varies in extreme temperatures, subzero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the tape is removed.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Crossweave High Tack Tape 08 December 2025

