

# Scaffold Debris Netting



## Product Specification

Air Permeability	60% approx
Colour	Green, Yellow & Black
Material	Polyethylene (HDPE), Monofilament
Tear Strength	56n / 5cm
Temperature Range	-40c to +70c
Tensile Strength	264n / 5cm
UV Performance	UV Stabilised 3%
Wind Coefficient	0.45
Weight (g/m2)	50gsm (+/-10%)

## Range

Code	Size
DEBRISBLACK	2m x 50m
DEBRISGREEN	2m x 50m
DEBRISYELLOW	2m x 50m

## Installation Instructions/Guidelines

- Debris netting should only be used once a full risk assessment has been carried out to assess suitability

## Handling & Storage

- Store in ambient conditions.

## Features & Benefits

- Lightweight and eyeleted design to allow quick and straightforward installation
- Open mesh netting reduces wind-loading on scaffold structures
- Designed to prevent accidents on site

## Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Scaffold Debris Netting 03 February 2026



0800 834 704 | 01625 855600  
enquiries@protection.co.uk  
www.protection.co.uk

