

White Debris Netting Flame Retardant



A polyethylene net material available in rolls, combines excellent tensile strength with superior puncture and tear resistance. FR Debris Netting can be adapted to fit virtually any type of structure and is widely used for containment during demolition projects. Debris netting is fixed in place using Cable Ties.

Features & Benefits

- Size: 2m x 50m
- Colour: White
- Spec: 60gsm
- Approx Weight : 6kg
- Coverage : 100 Square Metres

Product Specification

Colour	White
Material	Flame Retardant Reinforced Polyethylene
Roll Diameter	2m x 50m
Tensile Strength	Warp 720 N/32mm Weft 690 N/50mm
Weight (g/m2)	65gsm - 70gsm
Weight Per Roll	Approx 9.5kg

Installation Instructions/Guidelines

- External screening for scaffolding
- Can be installed horizontally or vertically

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [White Debris Netting Flame Retardant](#) 13 December 2025

