

Temporary Downpipe



OUR TEMPORARY DOWNPIPE SLEEVE ENSURES RAINWATER EFFECTIVELY DRAINS, TO AVOID DAMAGE TO PERMANENT FIXTURES.

Features & Benefits

- Manufactured from heavy-duty polythene for durability.
- Prevents damage and staining caused by rainwater.
- Easy to fix in place with included cable ties.
- Length available at 200m.
- Includes 25 free cable ties for easy installation and quick removal.

Product Specification

Colour	Clear with Protec Branding
Material	Lay Flat Tubing
Water Resistant	Yes
Weight Per Roll	8.5kg

Range

Code	Size
DOWNPIPE254X200	254mm x 200m

Installation Instructions/Guidelines

- Cut length to suit
- Secure in place with the cable tie the product is supplied with.
- Ensure the water collected has adequate drainage

Handling & Storage

- Store in ambient conditions.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [Temporary Downpipe 06 March 2025](#)



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

