

Duo Tape



Our double-sided tape makes fixing temporary protection materials onto flat surfaces hassle-free.

The strong, high-tack adhesive effectively adheres to protective materials like polythene, while the low-tack side provides reliable fixation to walls.

We offer a comprehensive range of fixing tapes suitable for various applications, ensuring versatility for different projects.

Please note that tape performance may vary depending on temperatures on site. Sub-zero or freezing temperatures may lead to reduced adhesion, while extremely high temperatures could leave behind adhesive residue.

Before applying any tape to finished surfaces, we recommend testing a small amount first. Additionally, avoid applying this tape to veneer doors and use a suitable protective Door Sleeve at all times.

Features & Benefits

- High tack adhesive on one side, Low-tack adhesive on the other.
- Hassle-free application for fixing temporary protection materials onto flat surfaces.
- Easy to tear and separate, providing convenience during use.

Product Specification

Colour	Blue
Material	Polythene
Temperature	-10 to +50 Degrees Celsius
Tensile Strength	17n/cm
Thickness	0.155mm
Weight Per Roll	0.4kg

Range

Code	Size
DUO 2 SIDED TAPE	50mm x 33m

Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test suitability. Please contact our technical department for specific advice
- We do not recommend applying any tape to veneer surfaces. Please contact our technical department for specific advice
- Ensure the surface is as clean as possible before applying the tape to create the strongest seal
- Inspect the tape at regular intervals to assess the level of adhesion

Handling & Storage

- Store in ambient conditions, please note the performance of tape varies in extreme temperatures, sub-zero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the tape is removed.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Duo Tape 16 May 2026



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

