

Digiscaff®



Product Specification		
Colour	White - Digitally printed to your design	
Material	Reinforced Flame Retardant	
	Polyethylene	
Tensile Strength	>630N/50mm	
Water Resistant	Yes	
Weight	16.5kg	
Weight (g/m2)	175gsm	

Range

Code	Size
Digiscaff	2m x 45m

DIGISCAFF® IS AVAILABLE AS PART OF OUR FULL GRAPHIC SCAFFOLDING DESIGN SERVICE.

Features & Benefits

- Premium grade flame retardant scaffold sheeting
- Digitally printed designs from 600mm 1800mm high
- Visible from long distances, ideal for high traffic areas
- Bespoke messages available for a minimum of 1 roll
- Flame retardant certified

Installation Instructions/Guidelines

• Follow separate installation guide

Handling & Storage

• Store in ambient conditions.

















Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Digiscaff® 20 August 2025

















