

Firescreen



Firescreen is manufactured with non-flammable woven glass fibre and coated on both sides with a specially formulated micronized aluminum polymer, this Flame Retardant Firescreen is ideal for situations where fire integrity is crucial.

It serves as a reliable barrier, making it suitable for construction sites, welding activities, and areas where abrasive work is performed.

Additionally, it offers heavy-duty floor protection while acting as a spark screen during welding and other hot works.

With the ability to provide up to one hour of integrity, it creates a non-flammable barrier, ensuring safety and security for both public and workspaces.

Features & Benefits

- Designed to halt the passage of smoke and flames for up to 60 minutes. IFC certification No: IFCC 1418
- SDP 21 (Non Rigid Fire Barrier) scheme, including fire testing of products to BS 476: Part 22: 1987
- Manufactured with non-flammable woven glass fibre.
- Coated on both sides with a specially formulated micronized aluminum polymer..
- Lightweight, flame retardant materials for straightforward installation.

Product Specification	
Colour	White
Flammability	BS.5438/6249 'A' Rating
Material	Woven glass fibre with micronized
	aluminium polymer coating.
Weight (g/m2)	450gsm
Weight Per Roll	15kg

Range

Code	Size
FIRESCREEN	1.3m x 25m

Certification

IFC Certification No: IFCC 1418 SDP 21 (Non Rigid Fire Barrier) scheme, including fire testing of products to BS 476: Part 22: 1987

Installation Instructions/Guidelines

• Follow safe working practices for your specific application

Handling & Storage

• Store in ambient conditions.

















Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Firescreen 28 November 2025

















