

Green Projoint Tape

Product Specification

Adhesion to Steel Plate	10.5 N/cm / 95.9 oz/in
Elongation at Break	20 %

Handling & Storage

- Store in moderate temperature and humidity environment.

Features & Benefits

- Good water resistance
- Good adhesion and strength
- Flexible and conformable
- Low moisture vapour transmission

Applications

Designed as a general purpose cloth tape for a full range of industrial and construction applications such as sealing, insulating, repairs, masking and bundling.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [Green Projoint Tape 05 June 2026](#)



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

