

Hazard Warning Tape



Product Specification

Colour	Black/Yellow, Red/White
Elongation at Break	>130%
Heat Resistance	-12C to 80C
Material	Heavy Duty PVC Film with Rubber Pressure Sensitive Adhesive
Peel Adhesion	>1.5N/cm
Weight	0.33kg

Range

Code	Size
HAZARDWARNINGTP	50mm x 33m
RED/WHITEHAZARD	50mm x 33m

Installation Instructions/Guidelines

- Before applying tape to a finished surface, a trial should be undertaken to test suitability
- Please contact our technical department for specific advice

Handling & Storage

- Store in ambient conditions.

Please note the performance of tape varies in extreme temperatures, sub-zero temperatures may cause lack of adhesion and high temperatures may cause adhesive residue to be left on the surface once the tape is removed.

Features & Benefits

- High visibility to highlight areas
- Excellent conformability
- Quick and easy to install
- Water resistant, can be used externally
- Durable and scuff resistant

Applications

Multi-purpose

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Hazard Warning Tape 11 February 2026



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

