

SafeRoute Hi-Vis Yellow Walkway Matting



Product Specification

Abrasion Resistance [mm ³]	250
Colour	Hi-Vis Yellow
Material	Rubber
Tensile Strength	3.0
Thickness	3mm
Water Resistant	Yes
Weight	32kg

Range

Code	Size
HIVISRUBBERMAT	-
HIVISWALKMATYLW	1m x 10m

Installation Instructions/Guidelines

- Clear the area of debris before laying out the roll
- Follow your safe working practice guidelines

Handling & Storage

- Follow your safe working practice guidelines

Features & Benefits

- Hi-Vis for increased prominence on site
- High grip and anti-slip multi directional tread to reduce slips and falls
- Strong and robust to withstand consistent traffic
- Reusable from site to site
- Can be pressure washed

Applications

Often used to denote the safe access route for traveling around site to avoid accidents.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: SafeRoute Hi-Vis Yellow Walkway Matting 02 July 2026



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

