

Stone Sill Protectors



Product Specification

Colour	Red
Internal Diameter	114mm (protects up to 250mm)
Length	2m
Material	Low Density PE Foam
Thickness	13mm
Weight	0.41kg per length

Range

Code	Size
JAMBTUBE114IDX2M-03	2m

Features & Benefits

- Flame Retardant certified.
- High density foam for superior impact protection.
- Flexible and easy to trim to size and shape.
- Reusable and multi-purpose.
- Protects stone sills during construction projects.

Certification

Flame Retardant - Certifire – Approved to TS63 - Certificate No. CF 5414

Installation Instructions/Guidelines

- Open the jamb profile down the pre-slit line
- Place the profile around the item that is being protected
- Unique self-gripping design avoids the need for additional fixings in the majority of applications
- If you do require additional fixing's please contact our technical team

Handling & Storage

- Store in ambient conditions.

Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: Stone Sill Protectors 10 May 2026



0800 834 704 | 01625 855600
enquiries@protection.co.uk
www.protection.co.uk

