

LadderHatch



Feat	ures	& B	ene	tits

- Provides safe access between floors on site.
- Prevents falls on site by blocking access.
- · Anti-slip checker plate lid.
- Access holes for the ladder reduce movement during use.
- Steel hinges for external use without corrosion.

Product Specification			
Colour	Red		
Material	High Grade Steel		
Weight	5.5kg		

Range

Code	Size
LadderHatch	Overall 770mmx620mm, opening sizes
	670mmx540mm, hole cut sizes
	570mmx720mm

Installation Instructions/Guidelines

- Create the opening in the floor between joists and ensure there is suitable support. Check the product sizes on site prior to cutting any openings as sizes may vary.
- Ladder Access Hatches can be screwed into place for additional security.
 Follow your safe working practices.
- Use the toggle catch to secure the door in an open position when in use.
- Always leave the checker lid closed when not in use to avoid trip hazards.

















Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: LadderHatch 28 November 2025

















